

## Wall and Roof Thimbles Insulated Model SMWT-I

### Applications and Performance

Insulated wall and roof thimbles are designed as per National Fire Protection Standards NFPA 37. The standard length of thimbles are 24" in total length with a fixed welded on wall mounting plate at 6". All thimble units come complete with two wall plates and rainguard.

### Selecting The Right Thimble

When selecting a proper size thimble for a given application, select the thimble based on the material Sch 40 pipe (P) or OD tubing (T).

Part Number	C		A		W		O		M		D		Weight	
	in	(mm)	in	(mm)	in	(mm)	in	(mm)	in	(mm)	in	(mm)	Lb	(Kg)
SMWT-2-P-I	2 5/8	(67)	14	(356)	16	(406)	20	(508)	6	(152)	24	(610)	103	(47)
SMWT-2.5-P-I	3 1/8	(79)	14	(356)	16	(406)	20	(508)	6	(152)	24	(610)	103	(47)
SMWT-3-P-I	3 5/8	(92)	16	(406)	18	(457)	22	(559)	6	(152)	24	(610)	111	(50)
SMWT-3.5-P-I	4 1/8	(105)	16	(406)	18	(457)	22	(559)	6	(152)	24	(610)	111	(50)
SMWT-4-P-I	4 5/8	(117)	16	(406)	18	(457)	22	(559)	6	(152)	24	(610)	125	(57)
SMWT-5-P-I	5 3/4	(146)	18	(457)	20	(508)	24	(610)	6	(152)	24	(610)	146	(66)
SMWT-6-P-I	6 3/4	(171)	18	(457)	20	(508)	24	(610)	6	(152)	24	(610)	146	(66)
SMWT-8-P-I	8 7/8	(225)	20	(508)	22	(559)	26	(660)	6	(152)	24	(610)	181	(82)
SMWT-10-P-I	11	(279)	22	(559)	24	(610)	28	(711)	6	(152)	24	(610)	203	(92)
SMWT-12-P-I	13	(330)	24	(610)	26	(660)	32	(813)	6	(152)	24	(610)	225	(102)
SMWT-14-P-I	14 1/4	(362)	26	(660)	28	(711)	34	(864)	6	(152)	24	(610)	251	(114)
SMWT-16-P-I	16 1/4	(413)	28	(711)	30	(762)	36	(914)	6	(152)	24	(610)	272	(124)
SMWT-18-P-I	18 1/4	(464)	30	(762)	32	(813)	38	(965)	6	(152)	24	(610)	302	(137)
SMWT-20-P-I	20 1/4	(514)	32	(813)	34	(864)	40	(1016)	6	(152)	24	(610)	315	(143)
SMWT-22-P-I	22 1/4	(565)	34	(864)	36	(914)	42	(1067)	6	(152)	24	(610)	337	(153)
SMWT-24-P-I	24 1/4	(616)	36	(914)	38	(965)	44	(1118)	6	(152)	24	(610)	344	(156)
SMWT-26-P-I	26 1/4	(667)	38	(965)	40	(1016)	46	(1168)	6	(152)	24	(610)	375	(170)
SMWT-28-P-I	28 1/4	(718)	40	(1016)	42	(1067)	48	(1219)	6	(152)	24	(610)	392	(178)
SMWT-30-P-I	30 1/4	(768)	42	(1067)	44	(1118)	50	(1270)	6	(152)	24	(610)	435	(198)

Part Number	C		A		W		O		M		D		Weight	
	in	(mm)	in	(mm)	in	(mm)	in	(mm)	in	(mm)	in	(mm)	Lb	(Kg)
SMWT-2-T-I	2 1/8	(54)	14	(356)	16	(406)	20	(508)	6	(152)	24	(610)	103	(47)
SMWT-2.5-T-I	2 5/8	(67)	14	(356)	16	(406)	20	(508)	6	(152)	24	(610)	103	(47)
SMWT-3-T-I	3 7/8	(98)	16	(406)	18	(457)	22	(559)	6	(152)	24	(610)	111	(50)
SMWT-3.5-T-I	3 5/8	(92)	16	(406)	18	(457)	22	(559)	6	(152)	24	(610)	111	(50)
SMWT-4-T-I	4 1/8	(105)	16	(406)	18	(457)	22	(559)	6	(152)	24	(610)	125	(57)
SMWT-5-T-I	5 1/8	(130)	18	(457)	20	(508)	24	(610)	6	(152)	24	(610)	146	(66)
SMWT-6-T-I	6 1/8	(156)	18	(457)	20	(508)	24	(610)	6	(152)	24	(610)	146	(66)

