

Wall and Roof Thimbles Un-Insulated Model SMWT

Applications and Performance

Un-Insulated wall and roof thimbles are not designed as per National Fire Protection Standards NFPA 37. The standard length of thimbles are 24" in total length with a fixed welded on wall mounting plate at 6". All thimble units come complete with two wall plates and rainguard.

Selecting The Right Thimble

In selecting a proper size thimble for a given application, select the thimble based on the material Sch 40 pipe (P) or OD tubing (T). Un-Insulated thimbles are designed for non-combustable wall/roof and for a maximum operating temperature of 1200°F/649°C. Thimbles can be built to any custom dimensions to suit any job application.

Part Number	C		A		W		O		M		D		Weight	
	in	(mm)	in	(mm)	in	(mm)	in	(mm)	in	(mm)	in	(mm)	Lb	(Kg)
SMWT-2-P	2 5/8	(67)	8	(203)	10	(254)	14	(356)	6	(152)	24	(610)	60	(27)
SMWT-2.5-P	3 1/8	(79)	8	(203)	10	(254)	14	(356)	6	(152)	24	(610)	60	(27)
SMWT-3-P	3 5/8	(92)	9	(229)	12	(305)	15	(381)	6	(152)	24	(610)	43	(20)
SMWT-3.5-P	4 1/8	(105)	10	(254)	12	(305)	16	(406)	6	(152)	24	(610)	43	(20)
SMWT-4-P	4 5/8	(117)	10	(254)	12	(305)	16	(406)	6	(152)	24	(610)	56	(25)
SMWT-5-P	5 3/4	(146)	12	(305)	14	(356)	18	(457)	6	(152)	24	(610)	72	(33)
SMWT-6-P	6 3/4	(171)	12	(305)	14	(356)	18	(457)	6	(152)	24	(610)	10	(5)
SMWT-8-P	8 7/8	(225)	14	(356)	16	(406)	20	(508)	6	(152)	24	(610)	83	(38)
SMWT-10-P	11	(279)	16	(406)	18	(457)	22	(559)	6	(152)	24	(610)	96	(44)
SMWT-12-P	13	(330)	18	(457)	18	(457)	24	(610)	6	(152)	24	(610)	108	(49)
SMWT-14-P	14 1/4	(362)	20	(508)	22	(559)	26	(660)	6	(152)	24	(610)	122	(55)
SMWT-16-P	16 1/4	(413)	22	(559)	24	(610)	28	(711)	6	(152)	24	(610)	143	(65)
SMWT-18-P	18 1/4	(464)	24	(610)	26	(660)	30	(762)	6	(152)	24	(610)	153	(70)
SMWT-20-P	20 1/4	(514)	26	(660)	28	(711)	32	(813)	6	(152)	24	(610)	162	(74)
SMWT-22-P	22 1/4	(565)	28	(711)	30	(762)	34	(864)	6	(152)	24	(610)	175	(80)
SMWT-24-P	24 1/4	(616)	30	(762)	32	(813)	36	(914)	6	(152)	24	(610)	188	(85)
SMWT-26-P	26 1/4	(667)	32	(813)	34	(864)	38	(965)	6	(152)	24	(610)	202	(92)
SMWT-28-P	28 1/4	(718)	34	(864)	36	(914)	40	(1016)	6	(152)	24	(610)	216	(98)
SMWT-30-P	30 1/4	(768)	36	(914)	38	(965)	42	(1067)	6	(152)	24	(610)	274	(125)

Part Number	C		A		W		O		M		D		Weight	
	in	(mm)	in	(mm)	in	(mm)	in	(mm)	in	(mm)	in	(mm)	Lb	(Kg)
SMWT-2-T	2 1/8	(54)	8	(203)	10	(254)	14	(356)	6	(152)	24	(610)	60	(27)
SMWT-2.5-T	2 5/8	(67)	8	(203)	10	(254)	14	(356)	6	(152)	24	(610)	60	(27)
SMWT-3-T	3 7/8	(98)	9	(229)	12	(305)	15	(381)	6	(152)	24	(610)	43	(20)
SMWT-3.5-T	3 5/8	(92)	10	(254)	12	(305)	16	(406)	6	(152)	24	(610)	43	(20)
SMWT-4-T	4 1/8	(105)	10	(254)	12	(305)	16	(406)	6	(152)	24	(610)	56	(25)
SMWT-5-T	5 1/8	(130)	12	(305)	14	(356)	18	(457)	6	(152)	24	(610)	72	(33)
SMWT-6-T	6 1/8	(156)	12	(305)	14	(356)	18	(457)	6	(152)	24	(610)	10	(5)

