

Flexible Connectors



SM101
ANSI to ANSI



SM102
ANSI to MALE NPT



SM103
ANSI to PLAIN PIPE

Model	Size (inches)	Model	Size (inches)	Model	Size (inches)
SM101-2-18	2	SM102-2-18	2	SM103-2.5-18	2.5
SM101-2.5-18	2.5	SM102-2.5-18	2.5	SM103-3-18	3
SM101-3-18	3	SM102-3-18	3	SM103-3.5-18	3.5
SM101-3.5-18	3.5	SM102-3.5-18	3.5	SM103-4-18	4
SM101-4-18	4	SM102-4-18	4	SM103-5-18	5
SM101-5-18	5	SM102-5-18	5	SM103-6-18	6
SM101-6-18	6	SM102-6-18	6	SM103-8-18	8
SM101-8-18	8			SM103-10-18	10
SM101-10-18	10				
SM101-12-18	12				
SM101-14-18	14				
SM101-16-18	16				
SM101-18-18	18				



SM104
SLIP-ON to SLIP-ON



SM105
ANSI to SLIP-ON



SM106
MALE NPT to FLARED LIP

Model	Size (inches)	Model	Size (inches)	Model	Size (inches)
SM104-2-18	2	SM105-2-18	2	SM106-4-18	4
SM104-2.5-18	2.5	SM105-2.5-18	2.5	SM106-5-18	5
SM104-3-18	3	SM105-3-18	3		
SM104-3.5-18	3.5	SM105-3.5-18	3.5		
SM104-4-18	4	SM105-4-18	4		
SM104-5-18	5	SM105-5-18	5		
SM104-6-18	6				

Sizes are in Inches unless specified otherwise. Standard overall length for flex connector is 18 inches. Corrugated flex is manufactured from stainless steel (321SS); Flex connectors are carbon steel. Stainless steel connectors are available upon request. ANSI floating flanges, custom connections and custom lengths to suit your application are also available. Flanges conform to ANSI#150 dimensions. Contact SMS for custom flex pricing.

Flexible Connectors



SM107

MALE NPT to MALE NPT



SM108

PLAIN PIPE to PLAIN PIPE



SM109

MALE NPT to OD TUBING

Model	Size (inches)	Model	Size (inches)	Model	Size (inches)
SM107-1.25-18	1.25	SM108-1.5-18	1.5	SM109-1.5-18	1.5
SM107-1.5-18	1.5	SM108-2-18	2	SM109-2-18	2
SM107-2-18	2	SM108-2.5-18	2.5	SM109-2.5-18	2.5
SM107-2.5-18	2.5	SM108-3-18	3	SM109-3-18	3
SM107-3-18	3	SM108-3.5-18	3.5	SM109-3.5-18	3.5
SM107-3.5-18	3.5	SM108-4-18	4	SM109-4-18	4
SM107-4-18	4	SM108-5-18	5	SM109-5-18	5
SM107-5-18	5	SM108-6-18	6	SM109-6-18	6
SM107-6-18	6	SM108-8-18	8		
		SM108-10-18	10		



SM110

ANSI to FEMALE NPT



SM111

ANSI to ANSI
braided fuel line



SM112

MALE NPT to MALE NPT
braided fuel line

Model	Size (inches)	Model	Size (inches)	Model	Size (inches)
SM110-1.5-18	1.5	SM111-3-18	3	SM112-0.5-18	0.5
SM110-2-18	2	SM111-4-18	4	SM112-0.75-18	0.75
SM110-2.5-18	2.5	SM111-5-18	5	SM112-1-18	1
SM110-3-18	3	SM111-6-18	6	SM112-1.25-18	1.25
SM110-3.5-18	3.5	SM111-8-18	8	SM112-1.55-18	1.55
SM110-4-18	4	SM111-10-18	10	SM112-2-18	2
SM110-5-18	5			SM112-2.5-18	2.5
SM110-6-18	6			SM112-3-18	3

Sizes are in Inches unless specified otherwise. Standard overall length for flex connector is 18 inches. Corrugated flex is manufactured from stainless steel (321SS); Flex connectors are carbon steel. Stainless steel connectors are available upon request. ANSI floating flanges, custom connections and custom lengths to suit your application are also available. Flanges conform to ANSI#150 dimensions. Contact SMS for custom flex pricing.

Flexible Connectors



SM113
MALE NPT to FEMALE NPT



SM114
MALE NPT to SLIP-ON



SM115
FEMALE NPT to OD TUBING

Model	Size (inches)	Model	Size (inches)	Model	Size (inches)
SM113-1.5-18	1.5	SM114-2-18	2	SM115-1.5-18	1.5
SM113-2-18	2	SM114-2.5-18	2.5	SM115-2-18	2
SM113-2.5-18	2.5	SM114-3-18	3	SM115-2.5-18	2.5
SM113-3-18	3	SM114-3.5-18	3.5	SM115-3-18	3
SM113-3.5-18	3.5	SM114-4-18	4	SM115-3.5-18	3.5
SM113-4-18	4	SM114-5-18	5	SM115-4-18	4
SM113-5-18	5			SM115-5-18	5



SM116
FEMALE NPT to SLIP-ON



SM117
SLIP-ON to TUBING



SM118
ANSI to TUBING

Model	Size (inches)	Model	Size (inches)	Model	Size (inches)
SM116-2-18	2	SM117-2-18	2	SM118-1.5-18	1.5
SM116-2.5-18	2.5	SM117-2.5-18	2.5	SM118-2-18	2
SM116-3-18	3	SM117-3-18	3	SM118-2.5-18	2.5
SM116-3.5-18	3.5	SM117-3.5-18	3.5	SM118-3-18	3
SM116-4-18	4	SM117-4-18	4	SM118-3.5-18	3.5
SM116-5-18	5	SM117-5-18	5	SM118-4-18	4
		SM117-6-18	6	SM118-5-18	5
				SM118-6-18	6

Sizes are in Inches unless specified otherwise. Standard overall length for flex connector is 18 inches. Corrugated flex is manufactured from stainless steel (321SS); Flex connectors are carbon steel. Stainless steel connectors are available upon request. ANSI floating flanges, custom connections and custom lengths to suit your application are also available. Flanges conform to ANSI#150 dimensions. Contact SMS for custom flex pricing.

Flexible Connectors



SM200
ANSI to ANSI 90 deg elbow



SM201
ANSI to TURBO FLANGE
90 deg elbow



SM202
ANSI to SLIP-ON 90 deg elbow

Model	Size (inches)	Model	Size (inches)	Model	Size (inches)
SM200-4-18	4	SM201-4-18	4	SM202-4-18	4
SM200-5-18	5	SM201-5-18	5	SM202-5-18	5
SM200-6-18	6	SM201-6-18	6	SM202-6-18	6



SM203
ANSI to MALE NPT 90
deg elbow



SM204
ANSI to FEMALE NPT
90 deg elbow



SM205
ANSI to SCH 40 PIPE
90 deg elbow

Model	Size (inches)	Model	Size (inches)	Model	Size (inches)
SM203-4-18	4	SM204-4-18	4	SM205-4-18	4
SM203-5-18	5	SM204-5-18	5	SM205-5-18	5
SM203-6-18	6	SM204-6-18	6	SM205-6-18	6



SM206
ANSI to TUBING
90 deg elbow

Model	Size (inches)
SM206-4-18	4
SM206-5-18	5
SM206-6-18	6

Sizes are in Inches unless specified otherwise. Standard overall length for flex connector is 18 inches. Corrugated flex is manufactured from stainless steel (321SS); Flex connectors are carbon steel. Stainless steel connectors are available upon request. ANSI floating flanges, custom connections and custom lengths to suit your application are also available. Flanges conform to ANSI#150 dimensions. Contact SMS for custom flex pricing.